

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number  
**WO 2005/093774 A2**

(51) International Patent Classification<sup>7</sup>: **H01J 5/00**

AA Eindhoven (NL). LINGEMANN, Erwin, N. [DE/DE];  
c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:  
PCT/IB2005/050851

(74) Agents: DUSSELDORP, Jan, C. et al.; Prof. Holstlaan 6,  
NL-5656 AA Eindhoven (NL).

(22) International Filing Date: 8 March 2005 (08.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
04101173.5 22 March 2004 (22.03.2004) EP

(71) Applicant (for all designated States except US): KONIN-  
KLJKE PHILIPS ELECTRONICS N.V. [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and


(75) Inventors/Applicants (for US only): PEETERS, Nicolas,  
G., A. [BE/BE]; c/o Prof. Holstlaan 6, NL-5656 AA Eind-  
hoven (NL). SCHELLEN, Johannes, A., T. [NL/NL]; c/o  
Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VOGT,  
Karl-Wilhelm [DE/DE]; c/o Prof. Holstlaan 6, NL-5656

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: ASSEMBLY OF A CAPPED HIGH-PRESSURE DISCHARGE LAMP AND A LAMP HOLDER



(57) Abstract: The invention relates to an assembly of a capped high-pressure discharge lamp (1) and a lamp holder (50). The discharge lamp comprises an outer envelope (10) in which a discharge vessel (11) is arranged. The outer envelope has a pinched portion (20) provided with a clamping member (25). A lamp cap comprises a substantially circular-cylindrical cup shaped portion for receiving the clamping member and is provided with a protruding collar (36). The lamp holder (50) comprises a substantially circular-cylindrical flange (55) for receiving the cup-shaped portion such that the flange engages the protruding collar. An inner diameter of the flange (55) has a tolerance of less than or equal to -0.2 mm. An outer diameter of the cup-shaped portion (33) has a tolerance of less than or equal to +0.2 mm. The respective tolerances extend over a length of at least 2.5 mm, measured with respect to the protruding collar.



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished  
upon receipt of that report*